

Denso Acrylic Topcoat

A component of the Denso Steelcoat Systems for the protection of above ground steelwork and storage tanks

Composition

Single pack waterborne synthetic copolymer coating.

Uses

Denso Acrylic Topcoat is suitable for use as a topcoat over Denso Ultraseal Tape and Denso Ultraseal RT Tape as part of the Denso Steelcoat Systems.

Service Temperature: -20°C to +80°C

Characteristics

Denso Acrylic Topcoat is:

- weather resistant,
- UV resistant, and
- single component.

Application

See *Instructions for Use* for additional detail. Ensure surfaces are clean and dry. Apply by brush.

Application Temperature: +3°C to +40°C

Availability

Denso Acrylic Topcoat is available in 15L drums in black and white colour. Other colours may be available on request.

Cleaning

Clean brushes and tools with water.

Storage conditions

Store in original packaging in cool, dry, frost-free, well ventilated conditions, out of direct sunlight and other major sources of heat. Expected shelf life is approximately 2 years.

Waste material

Please do not discard waste material, including packaging, in the surrounding environment. Please follow all relevant legislation for disposal.

Typical Properties

Specific Gravity	1.35
Solids (volume)	49%
Coverage (over Denso Ultraseal Tape or Denso Ultraseal RT Tape)	3 m ³ /litre
Drying time	
At 20°C	3 hours
At 3°C	24 hours

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).