

Denso Basecoat Kit

A tough protective outer coating

Composition

Denso Basecoat Kit is a two component hard wearing coating, consisting of a liquid portion containing synthetic polymers and waterproofing admixtures and a cementitious powder portion consisting of fine fillers.

Uses

Denso Basecoat Kit in conjunction with a suitable scrim is used to provide a tough protective outer coating over Denso Petrolatum Tapes and as the saturation coat on Denso Fabric backed tapes.

Service Temperature: -30°C to +60°C

Characteristics

- Durable and Weatherproof
- Excellent flexibility
- Good resistance to moderate trafficking

Application

See *Instructions for Use* for additional detail.
Apply by brush or roller.

Application Temperature: 0°C to +50°C

Typical Properties

Solids Content	33%
Specific Gravity	0.99
Drying Time	2 hours @ 25°C
Spread Rate	1.3 l/m ²

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 2008 (Certificate No. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI certificate 583748).

Page 1 of 1
Revision date: 27/01/2021