

Denso Clear Outerwrap

Light-duty Outerwrap for use with Denso tape systems

Composition

Denso Clear Outerwrap is a polyethylene film, supplied in roll form.

Uses

Denso Clear Outerwrap is used to isolate the pipe and prevent formation of adherent deposits. The wrap prevents operators from coming into contact with the underlying coating system.

Denso Clear Outerwrap is also used as a compression film for the Denso Glass Outerwrap range.

Characteristics

Denso Clear Outerwrap:

- is suitable for hand application,
- is suitable for immediate service,
- has excellent conformability,
- is not self-adhesive, and
- facilitates ease of handling coating systems.

Typical Properties

Appearance	Clear, stretchable film
Thickness	20 µm
Length	150 m
Width	100 mm

Warning

Plastic films can accumulate static electrical charge, take suitable precautions. Plastic films can suffocate if placed over the nose or mouth. To avoid danger of suffocation, keep product away from babies and children.

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate no. 583748).