

INSTRUCTIONS FOR USE**DESCRIPTION**

A polymer modified bituminous strip for use as an instant waterproof adhesive seal over cracks or failed reinstatement joints up to 5mm wide, on road pavements on secondary roads. The application of the tape prevents the ingress of water which causes cracking and severe fretting leading to the eventual breakdown of the asphalt pavement. The skid resistance can be increased by covering the tape with granite dust to a maximum size of 3mm providing a polished stone value similar to the existing road surface.

APPLICATION

- Remove dirt and debris from the cracks and surrounding road surface using a stiff broom or brush.
- Ensure that the road surface is dry. If necessary use a gas burner to dry the cracks and surrounding area.
- Apply Denso™ Overbanding Tape by hand or application roller following the line of the crack. When the crack is covered cut off from the roll and press the tape down thoroughly e.g. using hand or foot pressure. Remove the interleaving film from the tape. Where abrupt changes in direction occur, cut the tape and start a new section overlapping the end of the previous section by 50mm.

APPLICATION BY HAND

Peel back the interleaving film from the end of the roll and unwind it for one turn to expose the bitumen compound (as Fig 2). Apply the tape over the crack (as above). Press the tape down thoroughly and remove the interleaving.

APPLICATION BY TAPE APPLICATOR ROLLER

Fit the roll of tape onto the roll holder (as Fig 3) and screw the knurled nut clockwise to secure the roll in place.

Peel back the interleaving film from the end of the roll and unwind it for one turn to expose the bitumen compound (as Fig 2). Pass the tape around the application roller (as Fig 3). Push the roller along the line of the crack as shown (as Fig 4) to apply the tape centrally over the crack. Press the tape down thoroughly and remove the interleaving.

- In cold damp conditions apply a gas burner to warm the tape to improve adhesion to the road surface (Fig 5).
- Where required apply granite dust to improve the skid resistance. Traffic may flow immediately.

IMPORTANT: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore information given in these instructions for use is intended as a general guide and does not constitute a warranty, specification or risk assessment. Instructions for use are intended to provide sufficiently detailed information to achieve successful installation in normal circumstances. These guidelines may not cover all circumstances; however, our sales personnel are committed to assisting the user in establishing the suitability of the product for its intended purpose and additional specific information, advice and training (including Safety Data Sheets) is available. It is strongly recommended that installation is conducted with due regard to Health and Safety using a safe system of work, including risk assessments and method statements, in accordance with relevant local statutes and regulations. Equipment used for installation must be suitable for the intended use, maintained in a safe condition, inspected for signs of deterioration, and used by competent personnel. Any conflict between these guidelines and the specific project specifications must be resolved by the user before work commences. All rights reserved.

