



LEADERS IN CORROSION PREVENTION AND SEALING TECHNOLOGY

TECHNICAL DATA SHEET

OVER 130 YEARS SERVICE TO INDUSTRY



FM 01548 | EMS 583748

Premier Butyl™ Mastic

A cold applied, self-supporting mastic

Composition

Premier Butyl™ Mastic is based on butyl rubber.

Uses

Premier Butyl™ Mastic is used for moulding around irregular profiles such as flanges, mechanical joints and valves to provide a contour suitable for wrapping with Premier Butyl™ Tapes.

Characteristics

Premier Butyl™ Mastic is:

- suitable for service up to 50°C,
- permanently flexible,
- compatible with factory coatings of:
 - polyethylene,
 - polypropylene,
 - epoxy resin,
 - polyurethane, and
 - bitumen;
- easy to apply, and
- suitable for use in a wide range of climates.

Surface Preparation

see *Instructions for Use* for additional detail

Primer

Premier Butyl™ P16HT Primer

Application

see *Instructions for Use* for additional detail

Availability

Premier Butyl™ Mastic is available:
7x 1 kg bars, (approx. 450 x 52 x 32 mm)
12 rolls of 5 mm x 40 mm x 2 m.

Storage conditions

Store in a cool dry place in original packaging

Typical Properties

Colour	Black
Saponification no.	<2 mg KOH/g

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).

Revision date: 12/07/2017

Winn & Coales (Denso) Ltd
Denso House, Chapel Road,
London SE27 0TR, United Kingdom



Tel: +44 (0) 20 8670 7511
Fax: +44 (0) 20 8761 2456
Email: mail@denso.net Web: www.denso.net