

# Premier Butyl™ P16HT Primer

Primer for use with Premier Butyl™ Tapes

## Composition

Premier Butyl™ P16HT Primer is comprised of adhesive in hydrocarbon solvent.

## Uses

Premier Butyl™ P16HT Primer is used as primer for Premier Butyl™ tape systems.

## Application

See *Instructions for Use* for further details.

## Storage conditions

Store Premier Butyl™ P16HT Primer in a cool (+0°C to +30°C), dry place, in original packaging.

## Typical properties

Colour	Black
Density	0.78 g/cm <sup>2</sup>
Total solids	25%
Flash Point	-12°C
Consumption	4 m <sup>2</sup> /l
Saponification value	<10 mg KOH/g
VOC	600 g/l
Shelf life	2 years

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).

Page 1 of 1

Revision date: 07/01/2019

**Winn & Coales (Denso) Ltd**  
Denso House, Chapel Road,  
London SE27 0TR, United Kingdom



**Tel: +44 (0) 20 8670 7511**  
**Fax: +44 (0) 20 8761 2456**  
**Email: mail@denso.net Web: www.denso.net**