



Denso Primer D

Specialised primer designed for use with the Denso pipe-wrapping tapes

Composition

Fast-drying bitumen solution

Uses

Denso Primer D is a fast-drying primer that maintains surface cleanliness of the pipe prior to tape application.

Service Temperature: up to 75°C

Characteristics

Denso Primer D:

- improves cathodic disbondment resistance, and
- dries rapidly even in cool conditions.

Surface Preparation

Surfaces must be clean, dry and free from rust, scale and non-adherent coatings. Preferably, the area will be grit blasted or well wire brushed.

Application

See *Instructions for Use* for additional detail.

Application Temperature: 0°C to 55°C.

Availability

5 L, 25 L and 200 L drums.

Storage Conditions

Store all components upright in original packaging in a cool, dry, area. Keep away from heat, sparks and open flames.

Waste material

Please do not discard waste material, including packaging, in the surrounding environment. Please follow all relevant legislation for disposal.

Typical Properties

| | |
|------------------|---|
| Colour | Black |
| Viscosity | 200-500 cP |
| Solid Content | 58% w/w |
| Flash Point | >23°C |
| Specific gravity | 0.94 |
| Drying time | 10-15 minutes |
| Surface coverage | 9-11 m ² /L (@ DFT 45-60 µm) |

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).