

DENSOBANDTM

INSTRUCTIONS FOR USE

NOTE: DENSOBAND™ SHOULD ONLY BE APPLIED IN CONJUNCTION WITH HOT LAID ASPHALT.

SAFETY DATA SHEETS GIVING FULL INFORMATION ARE AVAILABLE.

JOINT SURFACE

The joint surface should be sawn for preference to present an even vertical face throughout its length.

CLEANING (see Fig 1.)

Do not apply Densoband to wet or oil contaminated surfaces.

- A. Ashpalt, concrete, kerbstone surfaces:
 - Clean with a stiff broom or wire brush to remove all dust, dirt, debris
- B. Metal surfaces such as road castings:
 Wire brush to remove all loose rust, dirt, etc.

PRIMING (see Fig 2.)

Apply Densoband[™] Primer to the vertical joint face and allow to dry.

APPLYING DENSOBAND (see Figs 3 & 4)

- A. Cut Densoband to length.
- B. Remove interleaving paper.
- C. Heat one surface of the Densoband with a gas torch.
- D. Apply the molten surface to the primed face using the applicator spatula or similar tool to assist adhesion. Densoband should stand
 5mm proud of the existing road surface. Trim flush to metal.
- E. Mitre Densoband into corners of right angle joints.

COMPACTION

After laying and levelling the new wearing course asphalt, the first pass of the roller should be along the joint edges, compacting the Densoband to form a 'rivet head'.

HEALTH AND SAFETY ADVICE

Densoband contains petroleum products which may affect the skin. Users are advised to:

- A. Ensure adequate ventilation during application.
- B. Wear gloves and protective clothing to protect against burns.
- C. Apply suitable barrier cream before working. In cases of contact with hot compound immerse in cold water.
- D. Wash thoroughly after use or before work breaks to remove compound from the skin.
- $\hbox{E.} \quad \hbox{Avoid use of diesel or other solvents for cleaning the skin.}$
- F. Change clothing when soiled.


Densoband Primer contains petroleum products which may affect the skin. Users are advised to: A - Avoid using in confined areas without air circulation. B - No smoking. C - Use gloves. Avoid prolonged contact with the skin. D - Wash hands after use. E - Change soiled clothing.


IMPORTANT:


Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore information given in these instructions for use is intended as a general guide and does not constitute a warranty, specification or risk assessment. Instructions for use are intended to provide sufficiently detailed information to achieve successful installation in normal circumstances. These guidelines may not cover all circumstances; however, our sales personnel are committed to assisting the user in establishing the suitability of the product for its intended purpose and additional specific information, advice and training (including Safety Data Sheets) is available. It is strongly recommended that installation is conducted with due regard to Health and Safety using a safe system of work, including risk assessments and method statements, in accordance with relevant local statutes and regulations. Equipment used for installation must be suitable for the intended use, maintained in a safe condition, inspected for signs of deterioration, and used by competent personnel. Any conflict between these guidelines and the specific project specifications must be resolved by the user before work commences. All rights reserved.



VERTICAL JOINT FACE FIG 1.







WINN & COALES (DENSO) LTD

Denso House, Chapel Road, London, United Kingdom TEL: +44 (0) 208 670 7511 • EMAIL: mail@denso.net

WEB: www.denso.net

