

Densostrip

Pre-formed bitumen sealing strip

Composition

Densostrip is a neutral compound based upon plasticised, high-melting point bitumen with inert siliceous fillers.

Uses

Densostrip is used to seal joints in pre-cast concrete units such as manhole rings, box culverts, tunnel and shaft segments, ogee pipes, etc.

Service temperature: -15°C to +40°C

Characteristics

Densostrip is:

- flexible,
- resistant to acids, alkali and salts,
- resistant to root penetration,
- resistant to microbial attack, and
- shows excellent adhesion to concrete.

Primer

Densostrip Primer

Application

See *Instructions for Use* for additional detail.

Application temperature: -5°C to +40°C.

Availability

Densostrip is available in reels. A wide selection of sizes is available to suit various joint designs.

Storage conditions

Store in a cool dry place in original packaging.

Waste material

Please do not discard waste material, including packaging, in the surrounding environment. Please follow all relevant legislation for disposal.

Typical Properties

Colour	Black
Non-volatile content	100%
Specific gravity	1.37
Specific volume	730 cm ³ /kg
Softening point	>100°C
Extensibility	600%

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).

Page 1 of 1

Revision date: 29/01/2018

Winn & Coales (Denso) Ltd
Denso House, Chapel Road,
London SE27 0TR, United Kingdom



Tel: +44 (0) 20 8670 7511
Fax: +44 (0) 20 8761 2456
Email: mail@denso.net Web: www.denso.net