

STEELCOAT 200™ SYSTEM



A petrolatum tape system for the protection of above ground pipelines operating at elevated service temperatures

The Steelcoat 200™ System comprises a polymer backed petrolatum tape (Denso Hotline™ Tape) and a high temperature mastic for sealing fittings in awkward shapes (Densoseal 16A™). No primer is required.

The system is designed to protect copper, iron or steel pipes that run at high temperatures, up to 110°C maximum (90°C if the pipe is buried), located above ground in ducts or set in concrete.

FEATURES

- No primer required
- Cold applied
- For service temperatures up to 110°C maximum
- Surface tolerant
- Can be applied by hand or wrapping machine

COMPONENTS

Denso Hotline™ Tape

Applied with a 55% overlap by either hand or machine application.

Densoseal 16A™

SURFACE PREPARATION

Minimal surface preparation required. Surfaces must be clean and dry. Remove all loose rust, scale and flaking coatings by hand wire brush.



PUB No. 494.05.2020

WINN & COALES (DENSO) LTD

TEL: +44 (0) 208 670 7511
FAX: +44 (0) 208 761 2456
EMAIL: mail@denso.net
WEB: www.denso.net

Winn & Coales (Denso) Ltd
33 - 35 Chapel Road
London SE27 0TR
UNITED KINGDOM



FM 01548 | EMS 583748
ISO 9001:2015 & ISO 14001:2015



A MEMBER OF WINN & COALES INTERNATIONAL