

Denso Ultraseal Tape

An acrylic coated bitumen tape for long-term corrosion protection.

Composition

Denso Ultraseal Tape is comprised of an acrylic coated non woven synthetic fibre fabric coated with a polymer bitumen adhesive compound on one side. It has a release paper interleaving which is removed during application.

Uses

Denso Ultraseal Tape is used for the protection of above ground steelwork from corrosion. It is a component of the Steelcoat System 400.

Service Temperature: +65°C maximum

Characteristics

Denso Ultraseal Tape is:

- suitable for use on above ground steelwork,
- part of the Steelcoat System 400 for corrosion protection, and
- contains no volatile components.

Typical Properties

Thickness	1.2 mm average	ASTM D1000
Weight	1.2 kg/m ² average	
Breaking Strength	3 N/mm	ASTM D1000
Elongation at Break	45%	ASTM D1000
Adhesion Peel strength		
<i>To steel</i>	2.0 N/mm	ASTM D1000 (24hrs)
<i>To self</i>	2.0 N/mm	

Application

See *Instructions for Use* for additional detail.

Recommended primer: Denso Penetrating Primer

Recommended topcoat: Denso Acrylic Topcoat

Application Temperature: +5°C to +50°C

Availability

Denso Ultraseal Tape is available in 15m rolls. Other sizes may be available on request.

Storage conditions

Store in a cool and dry place in original packaging.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).

Page 1 of 1
Revision date: 10/02/2021